
# EASYGATE LG


PREMIUM. STYLISH. FAST.



#### EASYGATE LG-1200







## **SPECIFICATIONS**

#### DIMENSIONS

| Standard:             | 1550mm(L) x 330mm(W) x 990mm(H) |
|-----------------------|---------------------------------|
| Wide:                 | 1550mm(L) x 510mm(W) x 990mm(H) |
| Barrier Height:       | up to 1800mm                    |
| Lane width:           | 1550mm/ 900mm                   |
| Gap Between barriers: | 80mm                            |
| MBTF:                 | 5,000,000 operations            |
| Warranty:             | 36 months                       |
| Sensors:              | Up to 40 sensor pairs           |
| Power Supply Input:   | 230 volts                       |
| Control Electronics:  | 12 V DC                         |
| Current:              | Standby 0.4 A                   |
| Consumption:          | Operational 6 A                 |



#### **EASYGATE LG-1800**



### AT A GLANCE

- Available models: EasyGate LG 1200 and LG 1800 with your choice of square or rounded cabinet
  Barrier opening time: from 0.4 seconds
  MTBF: of 5,000,000 operations
  36-month warranty
  DDA Compliant

| Operating Temp:                                       | 10°C to 50°C (with heater)   |
|---|--|
| Motor:  | 12 V DC  |
| Operation Mode:                                       | Normally Closed  |
| Control:  | Card In / Card Out Card In / No Exit Card In /<br>Free Exit Locked Free Passage                        |
| Pictograms:   | Wait Mode (White Indicator)<br>Access Granted (Green Indicator)<br>Illegal Transaction (Red Indicator) |
| Barrier Opening Time<br>(Standard lane):<br>MATERIALS | 0.4 Seconds  |
| Top Cover:  | Stainless Steel (other options)  |
| Middle Cover:   | Mild Steel Painted (other options)   |
| Front Cover:  | Stainless Steel  |
| Side Panels:  | Stainless Steel  |
| Frame:  | Steel  |

Specifications subject to change without prior notice.