



AT A GLANCE

- MTBF of 3,000,000 operations
- 24 month warranty
- Manufactured in Europe to ISO9001
- DDA Compliant

SPECIFICATIONS

DIMENSIONS

Standard:	1500mm(L) x 200mm(W) x 990mm(H)
Barrier Height:	800mm
Lane width:	550mm – 1000mm (customisable)
Gap Between barriers:	50mm
MBTF:	3,000,000 operations
Warranty:	24 months
Sensors:	Up to 36 sensor pairs
Power Supply Input:	230 volts
Control Electronics:	12 V DC
Current:	Standby 0.4 A
Consumption:	Operational 6 A

Operating Temp:	8°C to 50°C (with heater)
Motor:	12 V DC
Operation Mode:	Normally Closed
Control:	Card In / Card Out Card In / No Exit Card In / Free Exit Locked Free Passage
Pictograms:	Wait Mode (White Indicator) Access Granted (Green Indicator) Illegal Transaction (Red Indicator)
Barrier Opening Time (Standard lane):	0.7 Seconds
MATERIALS	
Top Cover:	White Corian (other options)
Front Cover:	Stainless Steel — Brushed or Polished
Side Panels:	Stainless Steel — Brushed or Polished
Frame:	Steel

Specifications subject to change without prior notice.